



NEROLAC IMPRESSIONS ECO CLEAN



PRODUCT DESCRIPTION

Nerolac Impressions Eco Clean, a water based luxury emulsion comes with Low VOC & almost No odour. Along with an ultra-rich HD finish & ease of maintenance, it makes living spaces healthier with strong bacterial and fungal resistance.

PERFORMANCE FEATURES & BENEFITS

	Anti-Bacterial		*Ultra Low Odour / VOC
	Rich Sheen		Rich Smooth Finish
	Excellent Fungal Resistance		Excellent Stain Resistance
	Excellent Washability		Excellent Flow & Brushability

*Paint with estimated VOCs in the range of 5 g/L without addition of colorant (Ref. KNPL Lab Results).
VOC content may vary from batch to batch.

SURFACE PREPARATION

1. Rub the surface using a suitable abrasive paper & wipe it off to ensure that the surface is clean, dry and free from dirt, grease, wax or any other defective or poorly adhering material.
2. Treat fungus-affected areas using Nerolac Fungicidal Solution & allow it to react for 6-8 h.
3. Apply a coat of suitable Primer** followed by Nerolac Wall Putty*** to level the dents and make the surface uniform. Sand the surface with emery paper 180 and wipe clean.
5. Again apply a coat of suitable primer**. Sand the surface with emery paper 320 and wipe clean.
7. Finally, apply 2-3 coats of Impressions Eco Clean emulsion as per recommended thinning. Dark shades may require additional coat for hiding.

RECOMMENDED USAGE

Nerolac Impressions Eco Clean Ultra Luxury Emulsion is designed for application on new as well as previously painted interior surfaces such as plaster, brickwork, cement rendering, concrete, hardboards, etc.

RECOMMENDED SYSTEM FOR APPLICATION

1. Primer** (1 coat), Dry in 4-6 h.
2. Putty***, Dry in 6-8 h.
3. Primer** (1 coat), Dry in 4-6 h.
4. Finish Nerolac Impressions Eco Clean Emulsion (2-3 Coats), Dry min. 4-6 h in between coats.

Sand the surface with Emery paper and clean before application of subsequent coat.

**Nerolac Premium or Popular Primer (Water thinnable / Solvent thinnable).

***Nerolac Wall putty or Nerolac Cement putty.

*Minimum 8 h for solvent thinnable primer & minimum 4-6 h for water thinnable Primer.

For Repainting on Smooth Lime/Distemper/Emulsion/Enamel Masonry Surfaces skip steps 1 & 2 and start with step 3.

PRECAUTIONS

1. Refer MSDS for 'Nerolac Impressions Eco Clean Ultra Luxury Emulsion' for safety measures & precautions.
2. Store in well ambient conditions, ventilated locations & away from sources of ignition and fire.
3. Keep away from children.
4. In case of eye / skin contact, wash with plenty of water.
5. Inhalation / Injection is dangerous. In either case, move to fresh air & consult a medical practitioner.
6. Do not apply when ambient temperature might drop to a level below 10°C within 4 h of application.
7. New plaster should be allowed to cure for minimum 12 weeks.
8. Avoid extra thinning for better results.
9. Can be tinted with Nerolac Hi-Power Universal Stainer before thinning. Do not add more than 5% of Nerolac Hi- Power Stainer. Stir the tinted paint well, after tinting & before application.
10. The container must be tightly closed when not in use. Stir well and strain before use.
11. Use safety equipment like rubber or polythene gloves, safety goggles / glasses & face mask.

TECHNICAL DATA



***Actual coverage may vary depending on method, condition of application, Type of Tools, Surface Porosity & Shade. Use of Felt Roller May reduce coverage upto 50%.

POST APPLICATION INSTRUCTIONS

For removing stains, sponge clean with a mild soap solution and wipe clean. Please allow 2 weeks of drying time to freshly painted wall for it to be ready for stain removal/cleaning.



SAFETY FEATURES

Non-Flammable



PACK SIZE

1 L, 4 L, 10 L & 20 L.



SHADE RANGE

As per Nerolac Colour Scapes Fandek & Shade Card

DISCLAIMER

The product information and application details given by the company has been provided in good faith and is meant to serve only as a general guideline during usage. The performance claims made are based on the tests carried out under controlled conditions and our past experience with the type of products. Therefore actual performance will depend on local factors prevailing at that point of time. Users are advised to carry-out sample tests by taking trials to ensure the suitability of products for their requirement prior to full-scale usage of our products.

The company is not liable for factors beyond its control such as application during adverse climatic conditions, use of improper application tools/techniques and surface preparation, any structural defects or the inferior quality of materials other than paints. The warranty/guarantee clauses shall accordingly be amended.