



NEROLAC

IMPRESSIONS ULTRA HD PREMIUM LUXURY EMULSION

NEROLAC

Colours that Care



PRODUCT DESCRIPTION

Ultra- High Definition Luxury Emulsion gives your walls a radiant sheen with Ultra HD colours and rich smooth finish with excellent washability, superior stain-resistance and ultra-low odour.

PERFORMANCE FEATURES & BENEFITS

	Radiant Sheen		Ultra High Definition Colours
	Rich Smooth Finish		Superior Stain Resistance
	Ultra Low Odour/VOC		Anti-Bacterial
	Excellent Washability		Excellent Flow & Brushability
	Fungal Resistance		

SURFACE PREPARATION

1. Remove all loose or Poorly adhering material, dirt, grease, wax etc. from the surface and apply a coat of suitable Nerolac Premium or Popular Primer (Water thinnable / Solvent thinnable).
2. Apply Nerolac Acrylic Wall Putty / Cement Putty to level the dents, dry, followed by sanding with emery paper 180 and wipe clean.
3. Apply another coat of Nerolac Premium or Popular Primer (Water thinnable / Solvent thinnable). After drying, sand the surface with emery paper No. 320 and wipe clean.
4. Dry minimum 8 h for solvent thinnable primer & minimum 4-6 h for water thinnable Primer.

RECOMMENDED SYSTEM FOR APPLICATION

1. Thin 1L paint with maximum 400-500 ml of water.
2. Apply 2-3 coats of Nerolac Impressions Ultra HD with an interval of 4-6 h by brush or roller.
3. Dark shade may require additional coat for hiding.

PRECAUTIONS

1. Refer MSDS for Nerolac Impressions Ultra HD Luxury Emulsion for safety measures & precautions.
2. Store in well ambient conditions, Ventilated locations & away from sources of ignition and fire.
3. Keep away from children.
4. In case of eye / skin contact, wash with plenty of water.
5. Inhalation / Injection will cause danger. In case move to fresh air & consult a medical practitioners in both the cases.
6. Do not apply when ambient temperature might drop to a level below 10°C within 4 h of application.
7. New plaster should be allowed to cure for minimum 12 weeks.
8. Avoid extra thinning for better results.
9. Do not use universal stainers. Stir well before paint application.
10. The container must be tightly closed when not in use.

TECHNICAL DATA



*** Actual coverage capacity may vary depending upon the method & condition of application, surface condition, temperature, wind velocity, application skills, surface roughness, surface porosity and shade.

*** Paint with estimated VOC in the range of 5g/L without addition of colorant (Ref: KNP lab results) .VOC content may vary from batch to batch.

POST APPLICATION INSTRUCTIONS

For removing stains, Sponge clean with mild soap solution and wipe clean. Please allow 2 weeks of drying time to freshly painted wall for it to be ready for stain removal/cleaning.

	<p>SAFETY FEATURES Non-Flammable</p>		<p>PACK SIZE 1 L, 4 L, 10 L & 20 L.</p>
	<p>SHADE RANGE As per Nerolac Colour Scapes Fandeck & Shade Card</p>		<p>SHELF LIFE 2 years from the date of manufacturing, when stored in the original tightly closed containers, away from direct unlight and excessive heat.</p>
	<p>HEALTH & SAFETY PRECAUTIONS Avoid inhalation, eye and skin contact. In case of contact, wash with water and Seek medical attention. Do not pour the leftovers in the drain. Dispose off after natural drying</p>		<p>STORAGE Store in a cool & dry place, Keep away from direct sunlight, Thinned paint to be consumed within 24 h after thinning</p>

DISCLAIMER

The product information and application details given by the company has been provided in good faith and is meant to serve only as a general guideline during usage. The performance claims made are based on the tests carried out under controlled conditions and our past experience with the type of products. Therefore actual performance will depend on local factors prevailing at that point of time. Users are advised to carry-out sample tests by taking trials to ensure the suitability of products for their requirement prior to full-scale usage of our products.

The company is not liable for factors beyond its control such as application during adverse climatic conditions, use of improper application tools/techniques and surface preparation, any structural defects or the inferior quality of materials other than paints. The warranty/guarantee clauses shall accordingly be amended.